

Effect of combined pulsed electric energy and high pressure homogenization on selective and energy efficient extraction of bio-molecules from microalga Parachlorella kessleri

Rui Zhang, Luc Marchal, Eugène Vorobiev, Nabil Grimi

▶ To cite this version:

Rui Zhang, Luc Marchal, Eugène Vorobiev, Nabil Grimi. Effect of combined pulsed electric energy and high pressure homogenization on selective and energy efficient extraction of bio-molecules from microalga Parachlorella kessleri. LWT - Food Science and Technology, 2021, 141, pp.110901. 10.1016/j.lwt.2021.110901. hal-04225106

HAL Id: hal-04225106 https://nantes-universite.hal.science/hal-04225106

Submitted on 22 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1 Effect of combined pulsed electric energy and high pressure

2 homogenization on selective and energy efficient extraction of

3 bio-molecules from microalga Parachlorella kessleri

- 4 Rui Zhang^{1,2*}, Luc Marchal³, Eugène Vorobiev², Nabil Grimi²
- 5
- ¹School of Food Science and Engineering, Wuhan Polytechnic University, Wuhan
 430023, China;
- ⁸ ²Sorbonne University, Université de Technologie de Compiègne, ESCOM, EA 4297
- 9 TIMR, Centre de recherche Royallieu CS 60319 60203 Compiègne cedex, France
- ¹⁰ ³LUNAM Université, CNRS, GEPEA, Université de Nantes, UMR6144, CRTT,
- 11 Boulevard de l'Université, BP 406, 44602 Saint-Nazaire Cedex, France ;
- 12
- 13 *Corresponding Author Address:
- 14 Mrs. Rui Zhang
- ¹School of Food Science and Engineering, Wuhan Polytechnic University, Wuhan 430023, China;
- 16 ²Sorbonne University, Université de Technologie de Compiègne, ESCOM, EA 4297 TIMR, Centre
- 17 de recherche Royallieu CS 60319 60203 Compiègne cedex, France
- 18 E-mail address: rui.zhang@utc.fr
- 19

20 Abstract

This work investigates the potential of pulsed electric energy (pulsed electric fields 21 (PEF) and high-voltage electrical discharges (HVED)) and high pressure 22 homogenization (HPH) for extraction of bio-molecules from Parachlorealla kessleri. 23 The applied procedures included individual pulsed electric energy (PEF, HVED), HPH 24 treatments, and their combination. The cell concentrations of suspension applied in PEF 25 or HVED treatment were 5 ~ 25 g/L, while 5 g/L suspension was always applied for 26 HPH treatment. The effects of applied procedures on the extraction of ionic components, 27 28 carbohydrates, proteins, and pigments were evaluated. The data evidenced that HVED treatment allowed selective extraction of ionic components and carbohydrates, while 29 HPH treatment was most efficient for simultaneous release all the bio-molecules. HPH 30 treatment (120 MPa, 10 passes) gave 4-fold higher content for pigments, 1.2-fold higher 31 content for carbohydrates and 6.5-fold higher content for proteins than HVED treatment 32 (40 kV/cm, 8 ms). For combined procedure, application of preliminary PEF or HVED 33 treatment with 5 g/L suspension allowed increasing the extraction of carbohydrates at 34 35 high energy consumption. By contrast, application of preliminary HVED treatment with 15 g/L or 25 g/L suspensions allowed enhancing extraction efficiencies of carbohydrates 36 and proteins, and reducing total energy consumption. 37

38 Keywords: Pulsed electric fields; High-voltage electrical discharges; Proteins, 39 Carbohydrates, Extraction

41 **1. Introduction**

Microalgae have been considered as a renewable feedstock for the food, feed and biofuel industries due to their rich composition, superior areal productivities compared to traditional crops and no dependence on fresh water and arable land (Garcia, Safi, Eppink, Wijffels, & Van, 2018). They can also rapidly accumulate biomass and produce desired bio-molecules by change culture growth conditions (like light, nutrient stress and nitrogen starvation, etc) and control their metabolism (Li et al., 2013).

The green microalga Parachlorella kessleri (P. kessleri) is a unicellular freshwater 48 organism (Chlorophyta) with a 2.5-10 µm mean diameter. However, the interesting bio-49 molecules of microalgae are commonly located either inside the cell cytoplasm or are 50 bound to cell membrane and require disintegration of cell wall before extraction (Garcia 51 et al., 2018). Some efforts have been done to break the microalgal cell wall by chemical 52 hydrolysis (Sedighi et al., 2019), high pressure disruption (Bernaerts, Gheysen, Foubert, 53 Hendrickx, & Van, 2019), ultrasound (Zhang, Grimi, Marchal, Lebovka, & Vorobiev, 54 2019), microwave (Chew, Chia, Lee, Zhu, & Show, 2019), or bead milling (Garcia et al., 55 2019), etc. However, these technologies refer to the use of severe processing conditions 56 that negatively affect the quality and purity of the extracts and complicating 57 downstream purification processes (Li et al., 2020; Martinez et al., 2019; Martinez, 58 Luengo, Saldana, Alvarez, & Raso, 2017). For example, mechanical disruption was 59 considered as highly energy inefficient, when conducted under laboratory conditions 60 and required a specific energy consumption of at least 33 MJ/kg dry biomass (Lee, 61

Lewis, & Ashman, 2012). These limitations have inspired numerous investigations of
alternative methods for recovery of bio-molecules from microalgae.

Recently, increasing interest has been focused on the use of pulsed electric fields 64 (PEF) to improve the extraction efficiencies of algal bio-molecules (Jaeschke et al., 65 2019; Martinez et al., 2019; Parniakov et al., 2015a). PEF treatment can cause the 66 increment of cell membrane permeability (electroporation) by applying high-intensity 67 68 electric field pulses of short duration (from µs to ms) (Puertolas & Barba, 2016). However, some research groups have also found that PEF was less effective for 69 extraction of proteins. More efficient extraction of proteins from microalgae required 70 more powerful disintegration of the cell walls, which can be provided by high voltage 71 electrical discharges (HVED) (Grimi et al., 2014). HVED treatment combines electrical 72 and mechanical effects for cell permeabilisation, can cause cell structure damage and 73 accelerate the extraction efficiencies of bio-molecules. Additionally, growing number of 74 researches have been focused on using the combined methods to achieve synergy 75 thereby increasing extraction efficiencies. For example, the use of US in combination 76 with microwave irradiation enhanced oil production from Chlorella vulgaris was 77 studied (Ma et al., 2015). Tavanandi, Mittal, Chandrasekhar, & Raghavarao (Tavanandi, 78 Mittal, Chandrasekhar, & Raghavarao, 2018) found that the combined US + freezing 79 and thawing method obtained the highest yield (91.62%) of C-Phycocyanin from 80 81 Arthospira platensis, while US (43.05%) or freezing and thawing alone (62.56%). Dejoye et al. (Dejoye et al., 2011) in their work used a combined microwave with 82

supercritical carbon dioxide (SCCO₂) extraction of lipids from *Chlorella vulgaris*,
which can be obtained the higher yield of lipid (4.73%) compared to SCCO₂ extraction
alone (1.81%).

However, to the best of our knowledge, the implementation of energy efficient cell 86 disintegration and selective extraction of microalgal bio-molecules remains largely 87 unexplored. This study investigated the effect of individual pulsed electric energy (PEF, 88 HVED) and HPH treatments, and their combination on the selective extraction of bio-89 molecules from P. kessleri. The dependence of recovery behaviors of ionic components, 90 pigments, carbohydrates and proteins on the different extraction procedures was 91 discussed. The distribution functions of microalgal cells were also observed. Finally, the 92 93 extraction efficiency in dependence of specific energy consumption and concentration of suspension were evaluated. 94

95 **2. Materials and methods**

96 2.1 Chemicals

D-glucose (98%) and bovine serum albumin (BSA, 98%) standard were provided
by Sigma-Aldrich (Saint-Quentin Fallavier, France). Bradford Dye Reagent was
purchased from Thermo Fisher (Kandel, Germany). Other chemicals of analytical grade
were obtained from VWR (Fontenay sous Bois, France).

101 2.2 Microalgae

102 Microalga P. kessleri was provided by AlgoSolis, Saint-Nazaire, France. The

microalga was obtained as frozen paste with moisture of $\approx 820 \text{ g H}_2\text{O}$ /kg fresh biomass. The major components of biomass include proteins ($\approx 440 \text{ g/kg}$ dry biomass), carbohydrates ($\approx 350 \text{ g/kg}$ dry biomass) and lipids ($\approx 38 \text{ g/kg}$ dry biomass), as well as host of other compounds (chlorophylls, carotenoids, polyphenols and minerals, etc) present in minor quantities. The pastes were first thawed at ambient temperature, and were washed 3 times by deionized water.

109 2.3 Extraction procedures

The applied extraction procedures included pulsed electric energy (PEF or HVED) treatments, HPH treatment, and pulsed electric energy followed by HPH treatment (i.e. PEF + HPH treatment or HVED + HPH treatment). The untreated (U procedure) suspension was also analyzed as the control experiment.

For individual PEF, HVED or HPH treatment, the suspension with the biomass concentration, C_m , of 5 g/L was always used (i.e. $C_m = 5$ g/L). The combined procedure involved using different concentrations of suspension in preliminary pulsed electric energy treatments as follows:

118 i) PEF (
$$C_m = 5 \text{ g/L}$$
) + HPH ($C_m = 5 \text{ g/L}$);

119 ii) HVED (
$$C_m = 5 \text{ g/L}$$
) + HPH ($C_m = 5 \text{ g/L}$);

120 iii) HVED (
$$C_m = 15 \text{ g/L or } 25 \text{ g/L}$$
) + HPH ($C_m = 5 \text{ g/L}$);

For all the combined procedure, a centrifugation step was carried out after pulsed electric energy treatments. Then the residue was re-suspended to 5 g/L suspension by deionized water, and then subjected to HPH treatment.

124 2.3.1. Pulsed electric energy (PEE) treatments

The pulsed electric energy treatments were made in PEF and HVED modes using 125 high voltage pulsed power 40 kV-10 kA generator (Basis, Saint-Quentin, France). PEF 126 treatment was performed in a batch one-liter cylindrical treatment chamber between two 127 plate electrodes. The distance between the electrodes was fixed at 2 cm to produce a 128 high PEF intensity of 20 kV/cm. HVED treatment was performed in the same treatment 129 chamber with a needle-plate geometry of electrode. The distance between the stainless 130 131 steel needle and the grounded plate electrode was fixed at 1 cm and the corresponding electric field strength of 40 kV/cm. The suspension with a total mass of 250 g was 132 introduced between the electrodes. The generator provided pulses of an exponential 133 form with a pulse repetition rate of 0.5 Hz (2 s between pulses: $\Delta t = 2$ s). Treatments 134 comprised application of n successive pulses. The exponential decay of voltage U \propto 135 exp. $(-t/t_p)$ with effective decay time $t_p \approx 10 \pm 0.1 \,\mu s$ were observed for applied modes 136 of treatment. The total treatment duration of pulsed electric energy, $t_e = nt_p$, was varied 137 within 0.01–8 ms (n = 1-800). Note that for extraction time of pulsed electric energy 138 was calculated as $t = n \times \Delta t$. Disrupted microalgal suspension characteristics were 139 140 measured between successive discharges or pulses. The temperature was maintained approximately at ambient temperature, and elevation of temperature not exceeded 5 °C. 141 Specific energy consumption, W (J/kg dry matter), was calculated for pulsed 142 electric energy using the following formula (Yu, Gouyo, Grimi, Bals, & Vorobiev, 2016): 143 $W = (n \times P_i)/m$ (1)

where *m* is the mass of the dry weight of biomass in suspension (kg), and P_i refers to the energy consumption of one electric pulse or discharge calculated from the following formula:

$$P_i = (C \times U^2)/2 \tag{2}$$

where *C* is the capacity of the capacitor, and *U* is the voltage of the generator. In this study, $P_i = 220$ J was applied for all the pulsed electric energy treatments.

149 2.3.2. High pressure homogenization (HPH) treatment

The HPH treatment was done using a NS 100L-PANDA 2K two-stage high pressure homogenizer (Niro Soavi S.p.A., Parma, Italy). The average throughput of the homogenizer was 10 L/h. The homogenizing pressure, p, and number of passes, N, were varied within the ranges 40-120 MPa, and 1-10 passes, respectively. The suspensions with a total mass of 250 g were processed. The initial temperature of suspensions before HPH treatment was approximately at ambient temperature and the cooling system to preclude the temperature elevation after HPH treatment never exceeded 5 °C.

157 Specific energy consumption, *W* (J/kg dry matter), was calculated for HPH 158 treatment using the following formula (Anand, Balasundaram, Pandit, & Harrison, 159 2007):

$$W = pN/C_m\rho \tag{3}$$

160 where $\rho ~(\approx 10^6 \text{ g/m}^3)$ is the density of the suspension.

161 2.4 Characterization

162 2.4.1 Particle size disruption

163 The particle size distribution (PSD) of cells was measured in the range from 0.01 to 164 3000 μ m by Malvern Mastersizer 2000 (Orsay, France). The calculated median meter 165 ($d_{(50)}$) was used to monitor the PSD of cells (See, Supplementary materials Fig. S1).

166 2.4.2 Ionic components

167 The electrical conductivity of suspensions was measured with digital
168 Conductivity/TDS meter (Thermo Fisher Scientific, Saint-Herblain, France) at 25°C.

169 2.4.3 Analyses of supernatant

The suspensions were centrifuged using a MiniSpin Plus Rotor F-45-12-11 (Eppendorf, Le Pecq, France) at 14,100 g for 10 min. The supernatants were collected for characterization analysis.

Absorption spectra were measured by a UV/VIS spectrophotometer (Thermo Scientific, Waltham, MA) within 350-900 nm against the blank (with the precision of \pm 1 nm). The pigments content was evaluated by analysis of the absorbance of peaks, *A*, at the wavelength of $\lambda \approx 680$ nm. This peak can be attributed to the absorbance of chlorophylls (Parniakov et al., 2015a).

The carbohydrates content, C_c , was measured using a phenol-sulfuric acid method (Dubois, Gilles, Hamilton, Rebers, & Smith, 1956). The proteins content, C_p , was measured using the method of Bradford (Bradford, 1976). The lipids content was 181 measured using the method of "whole cell analysis" (WCA) (Van Vooren et al., 2012). Briefly, the samples were first mixed with 20 µL distilled water and 10 µL butylated 182 hydroxytoluene (20 µg/uL) in clean vials. Then the mixture was suspended in 6 mL of a 183 CHCl₃: MeOH mixture (2:1, v/v). Vials were maintained for 6 h in the dark under slow 184 agitation. After extraction, the organic and aqueous phases were separated and the 185 solvent of the extracts was evaporated under N2 flux. 1 mL of CHCl3: MeOH mixture 186 (2:1, v/v) was then added and stored at -20 °C until analysis. Total fatty acids (TFA) 187 contents in the lipid extracts were quantified by Gas Chromatography-Flame Ionization 188 Detector (GC-FID) (Agilent Technologies Inc., Santa Clara, CA) analysis. Fatty acid 189 methyl ester (FAME) contents in the lipid extracts were quantified after a 190 191 transesterification step.

192 2.5 Statistical analysis

Each experiment was repeated at least three times. Data are expressed as mean \pm standard deviation. The error bars, presented on the figures, correspond to the standard deviations.

3. Results and discussion

197 *3.1 Extraction of bio-molecules*

Fig. 1 presents the changes of relative electrical conductivity, σ/σ_0 , and absorbance of pigments, *A*, (a), and the contents of carbohydrates, *C_c*, and proteins, *C_p*, (b), in the course of individual pulsed electric energy treatments. The data were compared between 201 PEF and HVED treatments. The application of PEF can significantly increase the relative electrical conductivity and the carbohydrates content as compared to the U 202 samples ($t_e = 0$ ms). The maximum values of $\sigma/\sigma_0 \approx 2.2$ and $C_c \approx 40.4$ mg/g were 203 obtained by using the longest electrical treatment duration, $t_e = 8$ ms. However, PEF 204 treatment at $t_e = 8$ ms only gave $A \approx 0.003$, and $C_p \approx 4$ mg/g, respectively. The data 205 evidenced that the PEF treatment was ineffective for extraction of pigments, and less 206 207 effective for extraction of proteins. In the study of Pataro et al., 2017), they report that the degree of cell membrane electroporation was not effective enough to 208 release proteins. This possibly reflects that PEF treatment was opening pores on cell 209 210 membranes, allowing release small-sized cytoplasmic proteins, but most proteins are larger and more bonded to the cell structure (Carullo et al., 2018). Moreover, some other 211 studies claimed to obtain higher amounts of proteins and pigments from 212 Nannochloropsis sp., but PEF treatment used in their studies was assisted with organic 213 solvent extraction (Parniakov et al., 2015b, 2015a). 214

In contrast, HVED treatment allowed enhance all measured values as compared to the U samples ($t_e = 0$ ms). The similar extraction behaviors were observed for ionic components, pigments, carbohydrates and proteins. All the measured values increased with the increase of t_e . HVED treatment at $t_e = 8$ ms resulted in the highest values of $\sigma/\sigma_0 \approx 3.1$, $A \approx 0.05$, $C_c \approx 83$ mg/g and $C_p \approx 22$ mg/g. Moreover, note that at $t_e = 6$ ms the measured values were reached the saturated level. Therefore, from the results of **Fig. 1**, it can be concluded that HVED treatment was more effective than PEF treatment for 222 the recovery of ionic components, pigments, carbohydrates and proteins. However, the spectral data evidenced that pigments extraction was practically absent after both 223 HVED and PEF treatments ($A \le 0.1$) since extracted chlorophylls are practically 224 insoluble in water. Their extraction required application of adapted solvents and more 225 intensive cell disruption technologies in the form of pigments-macromolecular water-226 soluble complexes. This result is in a good agreement with the work of Grimi et al. 227 (Grimi et al., 2014), who studied intracellular components recovery from microalgae 228 Nannochloropsis sp.. They find that electrically based disruption techniques were 229 ineffective for extraction of pigments. 230

Fig. 2 presents the changes of relative electrical conductivity, σ/σ_0 , and absorbance 231 of pigments, A, (a), and the content of carbohydrates, C_c , and proteins, C_p , (b) versus the 232 number of passes, N, for HPH treatment at different applied pressures, p = 40-120 MPa. 233 All the measured values increased with the increase of applied pressure, p, and number 234 of passes, N. The extraction for HPH treatment (120 MPa, N = 10) gave the highest 235 values of $\sigma/\sigma_0 \approx 1.9$, $A \approx 0.2$, $C_c \approx 102.6$ mg/g and $C_p \approx 144.2$ mg/g. Note that the 236 application of HPH treatment for N = 2 increased the value of σ/σ_0 up to ≈ 1.3 , 1.6, and 237 1.9 for p = 40, 80 and 120 MPa, respectively, and no further increase in σ/σ_0 was 238 observed with an increase of N (Fig. 2a). However, for pigments, carbohydrates and 239 proteins, the first four passes (N = 4) allowed obtaining a noticeable extraction 240 241 efficiencies for all applied pressures and further passes resulted in insignificant supplementary effects at high specific energy consumption. Therefore, in further 242

combination protocols N = 4 for HPH treatment was applied.

The obtained data showed that the extraction efficiencies of bio-molecules depend 244 dramatically on the used cell disruption techniques. The pulsed electric energy 245 treatments are more effective for recovery of ionic components than HPH treatment. For 246 both HVED and PEF treatments at $t_e = 8$ ms gave higher value of σ/σ_0 than HPH 247 treatment at 120 MPa for N = 10. Note that HVED was also very efficient for the 248 recovery of carbohydrates. HVED treatment at $t_e = 8$ ms gave the similar value of C_c 249 with P procedure for N = 4 at 120 MPa. However, HPH treatment can lead to the 250 intensive generation of cell debris and release of all the bio-molecules with increased 251 energy consumption. The application of HPH treatment (120 MPa, N = 10) gave 4-fold 252 higher content for pigments and 6.5-fold higher content for proteins as compared to 253 HVED treatment. The application of procedures that combine the important qualities of 254 pulsed electric energy and HPH treatments can be attractive in terms of extraction yield, 255 selectivity and energy consumption. 256

Fig. 3 compares the contents of carbohydrates, C_c , and proteins, C_p , versus the specific energy consumption, W, for treatment using combined pulsed electric energy and HPH treatments for diluted suspensions with $C_m = 5$ g/L. The treatment duration of pulsed electric energy treatments was $t_e = 2$ -8 ms, the applied pressure and number of HPH passes were 80 MPa and N = 4, respectively. The used combination procedure consisted in applying \approx 99-205 kJ/g dry matter of specific energy consumption. It was observed that HVED + HPH treatment showed higher values when compared to the

264 PEF + HPH treatment at the equivalent energy. The carbohydrates content increased with the energy consumption, the maximum value of $C_c \approx 151.9$ mg/g was observed for 265 HVED ($t_e = 8 \text{ ms}$) + HPH (80 MPa and N = 4) treatment with an energy input of ≈ 204.8 266 kJ/g dry matter. However, the maximum value of $C_p \approx 74.1$ mg/g was observed for 267 HVED ($t_e = 6 \text{ ms}$) + HPH treatment ($\approx 169.6 \text{ kJ/g}$ dry matter), further discharges 268 duration in the preliminary HVED treatment resulted in the slight decrease of proteins 269 content in final HPH treatment at high specific energy consumption. This reflects the 270 negative impact of HPH treatment on the microstructure of protein after HVED 271 treatment. A possible explanation for this phenomenon is that the irreversible binding to 272 the cell wall provoked by a longer duration of HVED treatment. However, it still needs 273 274 to be further proved and identified.

Note that for extraction of carbohydrates, the combined treatments can display 275 higher extraction efficiencies. For example, individual pulsed electric energy ($t_e = 4 \text{ ms}$) 276 or HPH (80 MPa, N = 4) treatment for extraction of carbohydrates, and gave $C_c \approx 34.4$ 277 mg/g (for PEF treatment), ≈ 66.6 mg/g (for HVED treatment) (Fig. 1b), and ≈ 65.2 278 mg/g (for HPH treatment) (**Fig. 2b**). However, the combined pulsed electric energy ($t_e =$ 279 4 ms) + HPH (80 MPa, N = 4) gave $C_c \approx 104.8$ mg/g (for preliminary PEF treatment) 280 and ≈ 135.2 mg/g (for preliminary HVED treatment) (Fig. 3). Similar behaviour was 281 also observed for combined pulsed electric energy ($t_e = 6 \text{ or } 8 \text{ ms}$) + HPH (80 MPa, N =282 283 4) treatments. However, the extraction of proteins for combined method was ineffective when compared with individual HPH treatment (80 MPa, N = 4). For example, 284

extraction of proteins using HPH treatment (80 MPa, N = 4) gave $C_p \approx 90.4 \text{ mg/g} (\approx 64$ kJ/g dry matter) (**Fig. 2b**), whereas PEF ($t_e = 4 \text{ ms}$) + HPH (80 MPa, N = 4) treatment gave $C_p \approx 56 \text{ mg/g}$ and HVED ($t_e = 4 \text{ ms}$) + HPH (80 MPa, N = 4) treatment gave $C_p \approx$ 63 mg/g at $\approx 134.4 \text{ kJ/g}$ dry matter (**Fig. 3**). Therefore, the application of individual PEF, HVED, HPH or combined treatment should be done based on the most suitable extraction selectivity, purity of extract and energy consumptions.

291 It was observed that the considerable specific energy consumption was needed for diluted suspensions ($C_m = 5$ g/L). For concentrated suspensions, the extraction can be 292 more effective in terms of energy consumption per g dry matter. Fig. 4 compares 293 extraction behaviours for carbohydrates and proteins after application of combined 294 procedure for concentrated suspensions. In these experiments, 15 g/L or 25 g/L 295 suspensions was used in the preliminary HVED treatment ($t_e = 6 \text{ ms}$; $\approx 35.2 \text{ and } 21.2$ 296 kJ/g dry matter, respectively), and then 5 g/L re-suspensions were used in the final HPH 297 treatment (40-120 MPa, N = 4). After the preliminary HVED treatment, the values of C_c 298 \approx 72.2 mg/g and $C_p \approx$ 20.6 mg/g were obtained for 15 g/L suspensions. For 25 g/L 299 suspensions, the values were observed for carbohydrates ($C_c \approx 71.8 \text{ mg/g}$) and proteins 300 $(C_p \approx 19.0 \text{ mg/g})$ (Fig. 4). Note that for 5 g/L suspensions, the similar preliminary 301 HVED treatment ($t_e = 6 \text{ ms}$, $\approx 105.6 \text{ kJ/g}$ dry matter) gave $C_c \approx 76.6 \text{ mg/g}$, $C_p \approx 20.4$ 302 mg/g (Fig. 3). The extracted contents of carbohydrates and proteins were not significant 303 304 different among different cell concentration of suspensions. This phenomenon was also observed in previously report (Safi et al., 2017), the authors investigated extraction of 305

water-soluble proteins from *Nannochloropsis gaditana* using PEF treatment. They reported the yield of proteins is statistically the same for used concentration of suspension ranging from 15 g/L to 45 g/L.

Moreover, the final HPH treatment at 40 MPa (≈ 83.2 kJ/g dry matter) increased the 309 values of C_c up to 113.7 mg/g and C_p up to 42.3 mg/g for 15 g/L suspensions (Fig. 4). 310 Similar behaviours were observed for 25 g/L suspensions using lower energy 311 consumption (\approx 69.1 kJ/g dry matter). Furthermore, the values of C_c and C_p 312 continuously increased with the increase of p or E for both 15 g/L and 25 g/L 313 suspensions. For example, at p = 80 MPa, they reached the values of $C_c \approx 141.9$ mg/g 314 and $C_p \approx 85.3$ mg/g for 15 g/L suspensions (≈ 131.2 kJ/g dry matter); and the values of 315 $C_c \approx 149.6 \text{ mg/g}$ and $C_p \approx 98.5 \text{ mg/g}$ for 25 g/L suspensions ($\approx 117.1 \text{ kJ/g}$ dry matter). 316 These values can be compared with the values of $C_c \approx 148.5 \text{ mg/g}$, and $C_p \approx 74.1 \text{ mg/g}$, 317 obtained using HVED ($t_e = 6 \text{ ms}$, $C_m = 5 \text{ g/L}$) + HPH (80 MPa, N = 4) treatment (\approx 318 169.6 kJ/g dry matter) (Fig. 3). Therefore, the preliminary HVED treatment of more 319 concentrated suspensions allowed increasing the extraction efficiency and decreasing 320 the energy consumptions. 321

322 *3.2 Selective carbohydrate release*

For characterization of relative selectivity of carbohydrates and proteins extraction, the selectivity ratio, $S = C_c/C_p$, was used. For non-selective extraction, the value of S = 1is expected. *S* can be regarded as a quality parameter for cell disruption processes, i.e., a higher selectivity for the desired product makes further fraction/purification processing 327 easier (e.g., less impurities) (Postma et al., 2017).

Fig. 5 presents the selectivity ratio, S, versus electrical treatment time, t_e , for 328 individual pulsed electric energy treatments and combined pulsed electric energy ($t_e = 2$ -329 8 ms) + HPH (80 MPa, 4 passes) treatment for diluted suspensions ($C_m = 5 \text{ g/L}$) (a), and 330 homogenizing pressure, p, for combined HVED ($t_e = 6 \text{ ms}$) + HPH (40-120 MPa, N = 4) 331 procedure for concentrated suspensions ($C_m = 15$ g/L or 25 g/L) (b). In our case, the 332 applied procedures were selective extraction towards carbohydrates (S > 1). The 333 selectivity ratio were smaller with the application of HPH treatment (S = 1-1.8) as 334 compared with pulsed electric energy treatments ($S \ge 3.5$). The means that the smallest 335 selectivity was obtained for extraction assisted with HPH treatment. The PEF treatment 336 gave on average the highest selectivity ratio, followed by the HVED treatment. 337 Therefore, for carbohydrates' selective release, the relatively mild cell disruption 338 technique is required. 339

Moreover, for the pulsed electric energy treatments with diluted suspension (C_m = 340 5 g/L), the values of S decrease with the increase of t_e (Fig. 5a). Note that the 341 application of pulsed electric energy treatments for $t_e = 6$ ms decreased the values to S 342 \approx 11 and $S \approx$ 4 for PEF and HVED treatment, respectively and no further decrease in S 343 was observed with an increase of t_e . This can be explained by a smaller quantity of 344 small-sized water-soluble proteins were released with the longer treatment time, 345 346 resulted in the decrease of S. However, the selectivity ratio in the final HPH treatment was almost stable (S = 1-1.5) regardless of applied t_e in preliminary pulsed electric 347

348 energy treatments (**Fig. 5a**).

Note that for HVED treatment ($t_e = 6$ ms), the similar values were observed ($S \approx 4$) 349 regardless of applied cell concentration (Fig. 5a and b). However, the values of S in 350 final HPH treatment applied p = 40 MPa (S = 1.8) were higher than that obtained from 351 final HPH treatment applied p = 80 or 120 MPa (S = 1) (Fig. 5b). This possibly reflects 352 that applied lower homogenizing pressure was less effective for microalgae cell damage 353 and release larger-size proteins. The finding agree with the previously study (Geciova, 354 Bury, & Jelen, 2002), who reported that pressures of HPH ranging from 55-200 MPa are 355 appropriate for the disruption of microbial cell. 356

Therefore, we can speculate that pulsed electric energy treatments allow selective release small-sized bio-molecules (e.g. ionic components, carbohydrates) resulting in relative pure fractions without negatively harming the other molecules.

360 **4. Conclusion**

An ideal extraction technique should be effective on extraction efficiency, energy 361 efficient and scalable. The present study provides an energy efficient method (combined 362 363 HVED + HPH treatment) for obtaining intracellular bio-molecules (carbohydrates and protiens) of P. kessleri with high extraction efficiency. The extraction efficiency and 364 energy consumption depends on the cell concentration of prior HVED treatment. The 365 increase of concentration from 5 g/L to 25 g/L resulted in \approx 5-fold decrease of HVED 366 energy consumption at approximately the same efficiency of extraction of carbohydrates 367 and proteins. Furthermore, HVED pre-treated more concentrated suspension (15 g/L or 368

369 25 g/L) underwent HPH allowed enhancing extraction efficiencies of proteins and 370 reducing total energy consumption, compared to HVED pre-treated diluted suspension 371 (5 g/L) followed by HPH. This promising method results can improve the recovery of 372 microalgae intracellular bio-molecules avoiding the use of solvents, reducing the energy 373 consumption of HPH.

374 Acknowledgments

Rui Zhang would like to acknowledge the financial support of China Scholarship Council for thesis fellowship. Outstanding young and middle-aged science and technology innovation team in Hubei Province (T2020012)

379 **References**

- Anand, H., Balasundaram, B., Pandit, A. B., & Harrison, S. T. L. (2007). The effect of
- 381 chemical pretreatment combined with mechanical disruption on the extent of
- disruption and release of intracellular protein from *E. coli. Biochemical*
- 383 *Engineering Journal*, *35*(2), 166–173.
- Bernaerts, T. M. M., Gheysen, L., Foubert, I., Hendrickx, M. E., & Van Loey, A. M.
- 385 (2019). Evaluating microalgal cell disruption upon ultra high pressure
- homogenization. *Algal Research*, 42, 101616.
- Bradford, M. M. (1976). A rapid and sensitive method for the quantitation of microgram
- quantities of protein utilizing the principle of protein-dye binding. *Analytical*
- *Biochemistry*, 72(1–2), 248–254.
- 390 Carullo, D., Abera, B. D., Casazza, A. A., Donsi, F., Perego, P., Ferrari, G., & Pataro, G.
- 391 (2018). Effect of pulsed electric fields and high pressure homogenization on the
- 392 aqueous extraction of intracellular compounds from the microalgae *Chlorella*
- 393 vulgaris. Algal Research, 31, 60–69.
- 394 Chew, K. W., Chia, S. R., Lee, S. Y., Zhu, L., & Show, P. L. (2019). Enhanced
- 395 microalgal protein extraction and purification using sustainable microwave-
- assisted multiphase partitioning technique. *Chemical Engineering Journal*, 367, 1–
 8.
- 398 Dejoye, C., Vian, M. A., Lumia, G., Bouscarle, C., Charton, F., & Chemat, F. (2011).

399	Combined extraction processes of lipid from Chlorella vulgaris microalgae:
400	microwave prior to supercritical carbon dioxide extraction. International Journal
401	of Molecular Sciences, 12(12), 9332–9341.
402	Dubois, M., Gilles, K. A., Hamilton, J. K., Rebers, P. A. t, & Smith, F. (1956).
403	Colorimetric method for determination of sugars and related substances. Analytical
404	Chemistry, 28(3), 350–356.
405	Duongbia, N., Chaiwongsar, S., Chaichana, C., & Chaiklangmuang, S. (2019). Acidic
406	hydrolysis performance and hydrolyzed lipid characterizations of wet Spirulina
407	platensis. Biomass Conversion and Biorefinery, 9(2), 305–319.
408	Garcia, E. S., Lo, C., Eppink, M. H. M., Wijffels, R. H., & van den Berg, C. (2019).
409	Understanding mild cell disintegration of microalgae in bead mills for the release
410	of biomolecules. Chemical Engineering Science, 203, 380-390.
411	Garcia, E. S., van Leeuwen, J., Safi, C., Sijtsma, L., Eppink, M. H. M., Wijffels, R. H.,
412	& van den Berg, C. (2018). Selective and energy efficient extraction of functional
413	proteins from microalgae for food applications. Bioresource Technology, 268,
414	197–203.
415	Geciova, J., Bury, D., & Jelen, P. (2002). Methods for disruption of microbial cells for
416	potential use in the dairy industry—a review. International Dairy Journal, 12(6),
417	541–553.
418	Grimi, N., Dubois, A., Marchal, L., Jubeau, S., Lebovka, N. I., & Vorobiev, E. (2014).

419 Selective extraction from microalgae *Nannochloropsis* sp. using different methods

420 of cell disruption. *Bioresource Technology*, *153*, 254–259.

- 421 Jaeschke, D. P., Mercali, G. D., Marczak, L. D. F., Müller, G., Frey, W., & Gusbeth, C.
- 422 (2019). Extraction of valuable compounds from *Arthrospira platensis* using pulsed
 423 electric field treatment. *Bioresource Technology*, 283, 207–212.
- 424 Lee, A. K., Lewis, D. M., & Ashman, P. J. (2012). Disruption of microalgal cells for the
- 425 extraction of lipids for biofuels: processes and specific energy requirements.
- 426 *Biomass and Bioenergy*, 46, 89–101.
- 427 Li, S., Li, J., Zhu, Z., Cheng, S., He, J., & Lamikanra, O. (2020). Soluble dietary fiber
- 428 and polyphenol complex in lotus root: Preparation, interaction and identification.
 429 *Food Chemistry*, *314*, 126219.
- 430 Li, X., Pvribyl, P., Bišová, K., Kawano, S., Cepák, V., Zachleder, V., & Vitová, M.
- 431 (2013). The microalga *Parachlorella kessleri*----A novel highly efficient lipid
- 432 producer. *Biotechnology and Bioengineering*, *110*(1), 97–107.
- 433 Lorenzo-Hernando, A., Ruiz-Vegas, J., Vega-Alegre, M., & Bolado-Rodriguez, S.

434 (2019). Recovery of proteins from biomass grown in pig manure microalgae-based

- 435 treatment plants by alkaline hydrolysis and acidic precipitation. *Bioresource*
- 436 *Technology*, 273, 599–607.
- 437 Ma, G., Hu, W., Pei, H., Jiang, L., Song, M., & Mu, R. (2015). In situ heterogeneous
- 438 transesterification of microalgae using combined ultrasound and microwave

irradiation. Energy Conversion and Management, 90, 41-46.

440	Martinez, Juan M, Delso, C., Alvarez, I., & Raso, J. (2019). Pulsed electric field
441	permeabilization and extraction of phycoerythrin from Porphyridium cruentum.
442	Algal Research, 37, 51–56.
443	Martinez, J. M., Gojkovic, Z., Ferro, L., Maza, M., Alvarez, I., Raso, J., & Funk, C.
444	(2019). Use of Pulsed Electric Field permeabilization to extract astaxanthin from
445	the Nordic microalga Haematococcus pluvialis. Bioresource Technology, 121694.
446	Martinez, J. M., Luengo, E., Saldana, G., Alvarez, I., & Raso, J. (2017). C-phycocyanin
447	extraction assisted by pulsed electric field from Artrosphira platensis. Food
448	Research International, 99, 1042–1047.
449	Parniakov, O., Barba, F. J., Grimi, N., Marchal, L., Jubeau, S., Lebovka, N., &
450	Vorobiev, E. (2015a). Pulsed electric field and pH assisted selective extraction of
451	intracellular components from microalgae Nannochloropsis. Algal Research, 8,
452	128-134. https://doi.org/10.1016/j.algal.2015.01.014
453	Parniakov, O., Barba, F. J., Grimi, N., Marchal, L., Jubeau, S., Lebovka, N., &
454	Vorobiev, E. (2015b). Pulsed electric field assisted extraction of nutritionally
455	valuable compounds from microalgae Nannochloropsis spp. using the binary
456	mixture of organic solvents and water. Innovative Food Science and Emerging
457	Technologies, 27, 79-85. https://doi.org/10.1016/j.ifset.2014.11.002
458	Pataro, G., Goettel, M., Straessner, R., Gusbeth, C., Ferrari, G., & Frey, W. (2017).

459	Effect of PEF treatment on extraction of valuable compounds from microalgae C .
460	vulgaris. Chemical Engineering Transactions, 57, 67–72.
461	Postma, P. R., Fernandes, D. A., Timmermans, R. A. H., Vermuë, M. H., Barbosa, M. J.,
462	Eppink, M. H. M.,Olivieri, G. (2017). Pulsed Electric Field for protein release
463	of the microalgae Chlorella vulgaris and Neochloris oleoabundans. Algal
464	Research, 24, 181–187.
465	Postma, P. R., Suarez-Garcia, E., Safi, C., Yonathan, K., Olivieri, G., Barbosa, M. J., &
466	Eppink, M. H. M. (2017). Energy efficient bead milling of microalgae: Effect of
467	bead size on disintegration and release of proteins and carbohydrates. Bioresource
468	Technology, 224, 670–679.
469	Puertolas, E., & Barba, F. J. (2016). Electrotechnologies applied to valorization of by-
470	products from food industry: Main findings, energy and economic cost of their
471	industrialization. Food and Bioproducts Processing, 100, 172-184.
472	Rivera, E. C., Montalescot, V., Viau, M., Drouin, D., Bourseau, P., Frappart, M., &
473	Couallier, E. (2018). Mechanical cell disruption of Parachlorella kessleri
474	microalgae: Impact on lipid fraction composition. Bioresource Technology, 256,
475	77–85.
476	Safi, C., Rodriguez, L. C., Mulder, W. J., Engelen-Smit, N., Spekking, W., den Broek,
477	L. A. M., & Sijtsma, L. (2017). Energy consumption and water-soluble protein
478	release by cell wall disruption of Nannochloropsis gaditana. Bioresource
479	Technology, 239, 204–210.

480	Sedighi, M., Jalili, H., Darvish, M., Sadeghi, S., & Ranaei-Siadat, SO. (2019).
481	Enzymatic hydrolysis of microalgae proteins using serine proteases: A study to
482	characterize kinetic parameters. Food Chemistry, 284, 334-339.
483	Skorupskaite, V., Makareviciene, V., Sendzikiene, E., & Gumbyte, M. (2019).
484	Microalgae Chlorella sp. cell disruption efficiency utilising ultrasonication and
485	ultrahomogenisation methods. Journal of Applied Phycology, 1-6.
486	Taleb, A., Legrand, J., Takache, H., Taha, S., & Pruvost, J. (2018). Investigation of lipid
487	production by nitrogen-starved Parachlorella kessleri under continuous
488	illumination and day/night cycles for biodiesel application. Journal of Applied
489	<i>Phycology</i> , <i>30</i> (2), 761–772.
490	Tavanandi, H. A., Mittal, R., Chandrasekhar, J., & Raghavarao, K. (2018). Simple and
491	efficient method for extraction of C-Phycocyanin from dry biomass of Arthospira
492	platensis. Algal Research, 31, 239–251.
493	Van Vooren, G., Le Grand, F., Legrand, J., Cuine, S., Peltier, G., & Pruvost, J. (2012).
494	Investigation of fatty acids accumulation in Nannochloropsis oculata for biodiesel
495	application. <i>Bioresource Technology</i> , 124, 421–432.
496	Yu, X., Gouyo, T., Grimi, N., Bals, O., & Vorobiev, E. (2016). Pulsed electric field
497	pretreatment of rapeseed green biomass (stems) to enhance pressing and
498	extractives recovery. Bioresource Technology, 199, 194-201.
499	Zhang, R., Grimi, N., Marchal, L., Lebovka, N., & Vorobiev, E. (2019). Effect of
	25

500	ultrasonication, high pressure homogenization and their combination on efficiency
501	of extraction of bio-molecules from microalgae Parachlorella kessleri. Algal
502	Research, 40, 101524.
503	Zhang, R., Grimi, N., Marchal, L., & Vorobiev, E. (2019). Application of high-voltage
504	electrical discharges and high-pressure homogenization for recovery of
505	intracellular compounds from microalgae Parachlorella kessleri. Bioprocess and
506	Biosystems Engineering, 42(1), 29–36.
507	Zocher, K., Lackmann, J.W., Volzke, J., Steil, L., Lalk, M., Weltmann, K.D., & Kolb, J.
508	F. (2019). Profiling microalgal protein extraction by microwave burst heating in
509	comparison to spark plasma exposures. Algal Research, 39, 101416.

511 **Figure captions**

512 **Fig. 1** Relative electrical conductivity, σ/σ_0 , after and before treatment, and absorbance

- of pigments, A, at the wavelength of $\lambda = 680$ nm (a), and the contents of carbohydrates,
- 514 C_c , and proteins, C_p , (b), versus PEE treatment time, t. The suspension's concentration
- 515 was $C_m = 5$ g/L. (PEE: pulsed electric energy)
- 517 Fig. 2 Relative electrical conductivity, σ/σ_0 , after and before treatment, and absorbance
- of pigments, A, at the wavelength of $\lambda = 680$ nm (a), and the contents of carbohydrates,
- 519 C_c , and proteins, C_p , (b), versus the number of HPH passes, N, at different pressures
- 520 (40–120 MPa). The suspension's concentration was $C_m = 5$ g/L dry matter. (HPH: high 521 pressure homogenization)

- **Fig. 3** The contents of carbohydrates, C_c , and proteins, C_p , versus the specific energy
- 524 consumption, W, for combined PEE (PEF or HVED; 2-8ms) and HPH (80 MPa, 4
- 525 passes) treatment. The suspension's concentration was $C_m = 5$ g/L dry matter. (PEE:
- 526 pulsed electric energy; HVED: high-voltage electrical discharges; PEF: pulsed electric
- 527 fields; HPH: high pressure homogenization)
- 528 (- : PEF; - : PEF+HPH; + : HVED; - : HVED+HPH)
- **Fig. 4** The content of carbohydrates, C_c , and proteins, C_p , versus the specific energy consumption, *W*, for combined HVED (15 or 25 g/L, 6 ms) and HPH (5 g/L, 40-120
- 531 MPa, 4 passes) treatment. (HVED: high-voltage electrical discharges; HPH: high

- 532 pressure homogenization)
- 533 (■: HVED (6 ms, 15 g/L); ▲: HVED (6 ms, 15 g/L)+HPH (40 MPa, 5 g/L);
- 534 **•** : HVED (6 ms, 15 g/L)+HPH (80 MPa, 5 g/L); HVED (6 ms, 15 g/L)+HPH (120
- 535 MPa, 5 g/L);
- 536 □: HVED (6 ms, 25 g/L); △: HVED (6 ms, 25 g/L)+HPH (40 MPa, 5 g/L);
- 537 ▷: HVED (6 ms, 25 g/L)+HPH (80 MPa, 5 g/L);◇: HVED (6 ms, 5 g/L)+HPH (120
- 538 MPa, 5 g/L))
- 539 Fig. 5 The selectivity ratio, S, versus electrical treatment time, t_e , for individual PEE
- 540 (PEF or HVED; 5 g/L, 2-8 ms) and combined PEE (PEF or HVED; 5 g/L, 2-8 ms) and
- 541 HPH (80 MPa, 4 passes) treatment (a), and versus homogenizing pressure, p, for
- 542 combined HVED (15 g/L or 25 g/L, 6 ms) + HPH (5 g/L, 40-120 MPa, 4 passes)
- 543 treatment (b). (PEE: pulsed electric energy; HVED: high-voltage electrical discharges;
- 544 PEF: pulsed electric fields; HPH: high pressure homogenization)
- 545 (a: ▲ : PEF; ▲ : PEF+HPH; : HVED; : HVED+HPH;
- 546 b: ★ :15 g/L; ★ : 25 g/L)



Fig. 1a



Fig. 1b





Fig. 2b









Graphical Abstract